

GroupThink Elite

GroupThink Elite is a Pan/Tilt/Zoom (PTZ) camera with USB video output.

It is equipped with a 1/2.7-inch HD Color CMOS with 2.1 mega pixel (16:9) and Full HD 1080p output resolution & a high dynamic image of 30 fps.

The superior 3x optical zoom lens, excellent white balance, and exposure mode delivers a clear image even in low light or the extreme contrast of brightness and darkness in a conference room

The camera covers a wide shooting angle and achieves high-speed, quiet, and precise positioning with smooth PTZ operations.

Key Features



Accurate, Smooth and Silent PTZ Movement

Along with 340-degree pan & 120-degree tilt rotation at adjustable speed and fast & accurate focus to capture any view in conferencing space.



3x Optical Zoom with 128° FOV

Using multi-element 3x lossless optical zoom lens, with 128-degree wide angle FOV (field of view).

Easy Plug and Play

Video output: USB2.0 Plug and play, Anyone can easily setup this USB Camera and control conferencing/ Live Streaming.



Compatibility

Simply connect a PC or Mac to conduct a meeting within the user's own familiar computing environment. Compatible with Mac and PC.

Product Specification

Model	GroupThink Elite
Image Sensor	1/2.7" HD Color CMOS
Effective Pixel	2.1 mega pixel (16:9)
Horizontal Resolution	1080P30/25, 720P30/25
Signal Standard	NTSC/PAL
Zoom	3x optical zoom
Focal Length	F=3.0mm(wide)-10.0(tele)
Horizontal Angle	Near-end 128°~Far-end 37°
Gain Control	Auto/manual
Focus	Auto/manual
SNR Ratio	≥50dB
Shutter Speed	8 to 1/10000s (auto)
Preset Position	IR remote control supports 9 presets PELCO Protocol supports 256 presets VISCA control support 64 presents
Pan/Tilt Movement Range	Pan: 340° (max speed 100°/S), Tilt: 120° (max speed 80°/S)
Control Terminal	RS-232, RS485
Control Protocol	VISCA, PELCO-D, PELCO-P (RS-232, RS485)
Video Output	USB
Video Compression Format	YUV, MJPEG, H.264
Noise Reduction	2D/3D
Work Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Baud Rate	9600/38400bps
Decoder	Built-in
Address Set	1~255
Installation	Support desktop, wall mount and ceiling mount and tripod installation
Power Supply	DC12V/ 2A
Power Consumption	12W
Net Weight/Gross Weight	1.46kg/2.85g
Dimension (LXWXH)	260×175×180 mm /296×255×223mm (before / after packing)
Accessories	DC 12V Power adaptor, IR remote control, Manual, RS232 cable, USB2.0 cable, Ceiling brackets & screws.