

# GroupThink Solo

**GroupThink Solo** Video Conference Webcam Plug and Play HD 1080p Camera with Built-In Speakerphone Web Camera. Integrated wide band audio speakerphone with noise cancellation and full duplex 360-degree Omni-directional mics working in 3-4 meter range. Features in advanced Digital Signal Processing of echo cancellation and Noise suppression technology to ensure excellent audio clarity on both ends of the line.

All these features make it the perfect solution for spontaneous conferencing and collaboration which is compatible with various telecommunication platforms

## Key Features



### HD Camera

Equipped with 1/2.7" HD color CMOS Sensor, 2.1 Mega pixel achieved full HD 1080p @25fps vivid video quality, with wide view angle FOV 105-degree lens is perfect for group of 1-6 meeting room.



### Microphone

Integrated wide band audio speakerphone with noise cancellation and full duplex 360-degree Omni-directional mics working in 3-4 meter range



### Speaker

Features in advanced Digital Signal Processing of echo cancellation and Noise suppression technology to ensure excellent audio clarity on both ends of the line. Speaker power output 5 watts



### Portability

Take video conferencing on the go. Carry your item from meeting to meeting, or pack it when traveling so you never miss the opportunity to meet face to face.

# Product Specification

Model	GroupThink Solo
Sensor	1/2.7" HD color CMOS
Effective Pix	2.1 Megapixel
Min. Illumination	0.5 Lux at F2.0
Min. Illumination	Auto
Gain control	Auto
Focus	2.3 mm
Iris	Fixed
Zoom	Fixed Lens
Horizontal View Angle	105 Degree
Video Output	MJPEG
Video Output Format	MJPEG:1080P25,720P25, 640x480
Image Control	UVC
Horizontal Rotation	N/A
Vertical Rotation	Roller rotation -10~+10 degree
Audio Type	Full duplex Omnidirectional Microphone
Sensitivity	-26BFS
S/N Ratio	61dB
Frequency Range	20HZ~15kHz
Speaker	Built in powerful Speaker, AGC provided excellent audio quality
Speaker Power	5W power consumption, diameter 52mm
Echo Cancellation	Advanced Echo Cancellation up to 256 mm
Noise Suppression	> 15db
Sampling Rate	16kHz /48k HZ